

# DWC/C-HT



## DWC/C-HT BEST-IN-CLASS PERFORMANCES SOLVE YOUR EXTRA TORQUE REQUIREMENTS

- Tough: ideal for operators who need more torque
- Dependable: torque ratings validated with physical testing
- Trouble-Free: compatible with DWC/C and Buttress
- Quality: manufactured on premium threading lines
- From the people you trust: VAM technical support, wide licensee network, assistance from VAM Field Service at the rig site

## VALIDATED PERFORMANCE PROPERTIES

Size OD	Nominal Weight	Wall Thickness	Drift Diameter	Coupling OD	Connection Tension and Compression Efficiency	Connection Yield Torque (ft-lbs)			
						T95	P110	P110EC	Q125
inch	lb/ft	inch	inch	inch	%				
4.500	10.50	0.224	3.927	5.000	100.0	7,100	7,800	8,500	8,500
4.500	11.60	0.250	3.875	5.000	100.0	8,500	9,400	10,300	10,300
4.500	12.60	0.271	3.833	5.000	100.0	9,400	10,500	11,500	11,500
4.500	13.50	0.290	3.795	5.000	100.0	10,300	11,400	12,600	12,600
4.500	15.10	0.337	3.701	5.000	98.7	12,600	14,000	15,500	15,500
5.000	15.00	0.296	4.283	5.563	100.0	14,000	15,500	17,000	17,000
5.000	18.00	0.362	4.151	5.563	100.0	18,000	20,100	22,200	22,200
5.000	20.30	0.408	4.059	5.563	92.9	20,200	22,600	25,000	25,000
5.000	20.80	0.422	4.031	5.563	90.1	20,700	23,200	25,700	25,700
5.000	21.40	0.437	4.001	5.563	87.3	21,300	23,900	26,500	26,500
5.000	23.20	0.478	3.919	5.563	80.5	22,600	25,400	28,200	28,200
5.000	24.10	0.500	3.875	5.563	77.3	23,300	26,200	29,100	29,100
5.500	15.50	0.275	4.825	6.050	100.0	14,300	15,900	17,500	17,500
5.500	17.00	0.304	4.767	6.050	100.0	16,700	18,700	20,600	20,600
5.500	20.00	0.361	4.653	6.050	100.0	21,200	23,800	26,300	26,300
5.500	23.00	0.415	4.545	6.050	89.0	24,700	27,800	30,800	30,800
5.500	26.00	0.476	4.423	6.050	78.5	27,600	31,200	34,700	34,700
5.500	26.80	0.500	4.375	6.050	75.1	28,700	32,400	36,100	36,100

VAM® is a registered trade mark of VALLOUREC MANNESMANN Oil & Gas France

